



**Model: KOT-0121U-SA4BP**

**12.1" LCD Open Frame SAW Touch Monitor  
(The Dust-proof Type)**

### **Product Feature**


- ◆ Long lasting product cycle enclosure controlled by KeeTouch specifications .
- ◆ Future generation panels phased-in without external changes.
- ◆ High quality panel with high brightness, high contrast ratio and broad viewing angle.
- ◆ Multiple mounting options including horizontal bracket-mount, vertical bracket mount and VESA mount.
- ◆ KeeTouch's SAW technology on pure glass for the ultimate in image quality.
- ◆ Finger or gloved hand operation.
- ◆ VGA and DVI and HDMI input video format.
- ◆ USB touch interface port.

## Specification

<b>Model No.</b>	KOT-0121U-SA4BP	
<b>Series</b>	OT, Dust-proof	
<b>Display Type</b>	4:3 Ratio 12.1" Active matrix TFT-LCD	
<b>Display Active Area</b>	245.7×184.275(mm)	
<b>Monitor Dimensions</b>	<b>Width:</b> 281mm <b>Height:</b> 219.5mm <b>Depth:</b> 44.5mm	
<b>Suggested Resolution</b>	1400×1050@60Hz	
<b>Support Colors</b>	16.2M	
<b>Brightness(Typ.)</b>	Pure LCD Panel	350cd/m <sup>2</sup>
	With SAW Glass screen	315cd/m <sup>2</sup>
<b>Viewing Angle (Typ.at CR&gt;10)</b>	Horizontal(left/right)	80°/80°
	Vertical(up/down)	80°/45°
<b>Video Input</b>	VGA DVI HDMI	
<b>Frequency(H/V)</b>	30~80KHz / 60~75Hz	
<b>Power Supply</b>	Type:Externalbrick Input (line) voltage: 100-240 VAC, 50-60 Hz	
<b>Environment</b>	Operating Temp.	0~50°C
	Storage Temp.	-20~60°C
	Operating RH:	20%~80%
	Storage RH:	10%~90%
<b>Weight(N.W/G.W)</b>	2.5Kg(1pcs)/5.5Kg (2pcs in one package)(Approx.)	
<b>Package Dimensions</b>	373(L)*170(W)*317(H)mm (2pcs in one package)	
<b>Power Consumption</b>	10W Max	
<b>Standby Power Consumption</b>	1.5W	
<b>Mount Interface</b>	Mount bracket, horizontal or vertical and VESA mount (Standard mount brackets are supplied)	
<b>OSD Control</b>	Buttons	AUTO,+,POWER,-,MENU
	Function	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
<b>Touch Screen Type</b>	KeeTouch 12.1" SAW 4mm touch screen	
<b>Touch System Interface</b>	USB	
<b>Agency Approval</b>	CCC,ETL,FCC,CE,CB,RoHS	
<b>Regular Warranty</b>	1 Year	

NOTE: The display SPEC. will change follow the relevant LCD panel brand and model

## Mechanical Dimensions



## Record of Revision

Version	Date	Description
1.0	2017/06/07	Initial Release