

## Product Feature

- ◆ 55 "commercial grade projected capacitive multi touch display" designed for retail, shopping malls, transportation, education, digital signage and other industries.
- ◆ The effect of pure plane makes the whole machine have elegant and fashionable appearance.
- ◆ Sturdy structural design and flexible installation methods can be conveniently installed in various applications.
- ◆ ETL, FCC, CE, CB, RoHS, CCC certificates.



**55" all- in-one PCAP touch monitor**

The Commercial High Definition LCD panel with LED backlight provides the user with high definition and highlighting display effect, reduces the power consumption of the whole machine and makes the whole machine lighter and thinner.

It supports built-in plug-in OPS module, and users can build their application system very conveniently. KeeTouch provides a variety of specifications of OPS

## Applications

- ◆ Banking terminal
- ◆ POS, POI terminals
- ◆ Point-of-services
- ◆ Customer loyalty systems
- ◆ In-store display
- ◆ Hospitality display
- ◆ Support OEM

<b>Specification</b>	55 inch Wall-Mount Touch Display
<b>Model</b>	KTP-550M-001
<b>Diagonal Size</b>	54.64" (1387.8mm)
<b>Aspect Ratio</b>	16:9
<b>Dimensions and weight</b>	TBD
<b>Touch Technology</b>	Projected Capacitive touch technology
<b>LCD Technology</b>	Active matrix TFT LCD with LED backlight
<b>Native Resolution</b>	1920 × 1080 @ 60 Hz
<b>Other Supported Resolutions</b>	640 × 480 @ 60Hz 800×600 @ 60 Hz 1024×768@ 60Hz 1366×768 @ 60 Hz 1440×900 @ 60 Hz 1680× 1050 @ 60 Hz
<b>Colors</b>	16.7 millions
<b>Brightness</b>	400 nits
<b>Response Time</b>	6.5 ms
<b>Viewing Angle</b>	Horizontal:±89°or 178° ; Vertical: ±89°or 178°
<b>Contrast Ratio</b>	1000:1
<b>Touchscreen Transparency</b>	>86%
<b>Touch Surface Hardness</b>	>7 H
<b>Touch Response Time</b>	≤12 ms
<b>Input Methods</b>	Finger or capacitive pen
<b>Interface</b>	HDMI*1,OPS*1, YPBPR*1, VGA*1, Audio in*1, CVBS*1, USB Media(A Type), USB Touch (B Type)
<b>Power Supply</b>	AC 100V ~ 240V (50/60 Hz)
<b>Power Consumption</b>	Max: 95 W (without OPS)
<b>Installation</b>	VESA 400mm x 400mm, stand mount, wall mount
<b>Temperature</b>	Operating:0°C~40°C, Storage:-20°C~60°C
<b>Humidity</b>	Operating:20%~80%, Storage:10%~90%
<b>Altitude</b>	<3000 m
<b>Accessories</b>	VGA cable, USB cable, power cable, OPS
<b>Warranty</b>	1 Year

**NOTE: The display SPEC. will change follow the relevant LCD panel brand and model**

Add: Level1, 3, 4, BLD 9, Luck-King Industry Park Gongyedong Road, Longhua District, Shenzhen 518109, P. R. China

Tel: +86-755-82599797

Fax: +86-755-82599968

E-mail: sales@keetouch.com

www.keetouch.com